

Automatic Strapping Machine

SV-5000




Features

- Capable up to 50 straps/minute
- PLC controlled with diagnostics
- Electronic reel brake
- Electronic tensioning
- Movable magnetic pendant
- Loop ejector
- Long life heater blade
- Power saving system, motor runs only during cycle
- Easy access strap path (no tools)
- Auto refeed
- Choice of arch sizes & strap widths

Specifications

Minimum Package Size:	4" x 4"
Maximum Package Size:	Within arch size
Maximum Tension:	150 lbs.
Table Top Height:	Standard: 30"
Optional:	27"
Electrical Supply:	110 VAC, 15A
Core Sizes:	8"x8" or 9"x8"
Strap Sizes:	1/4", 3/8" polypropylene Metric: 5, 6, 7, 9mm polypropylene
Weight:	440 lbs.

**Servo-Motor Technology
With Automatic Loading!**



Servo-Motor Technology

**Easy Access Fold Open
Roller Tops**



Push Button Auto Load



Movable Magnetic Pendant

SV 5000				
		WIDTH		
HEIGHT		25	33	41
	15			
	23			
	31			
	39			

LEGEND	
	STOCK

New Polychem Long Length Polypropylene Strapping

The SV-5000 is capable of using extra long length coils for greater productivity

Polychem Polypropylene Plastic Strapping • Up to 50% MORE FOOTAGE PER COIL!

- Save time and money
- Lower cost per foot
- Fewer coil changes
- MAS50XLY Yellow 5mm x 30,000 feet
- MAS61XLY Yellow 6mm x 26,000 feet
- MAS90XLY Yellow 9mm x 18,000 feet

STRAPPING EQUIPMENT

Automatic Strapping Machine

GP-44



Features

- Capable of up to 44 straps/minute
- PLC controlled with diagnostics
- Outside reel with automatic, waist-high strap loading
- Electric, no-adjust reel brake
- Movable, magnetic control box to facilitate any operation position
- Safety switches on table tops and front door
- Loop ejector to eject accidentally actuated straps
- Long life heater blade with smoke exhaust system

Specifications

Strapping Speed:	Up to 44 straps/minute
Tension:	External, fully adjustable range
Power:	110 volt single phase, others available
Strap Sizes:	1/4", 3/8", 1/2", polypropylene Metric: 5, 6, 7, 9, 12mm polypropylene
Core Sizes:	8"x8" or 9"x8"
Table Top Height:	31", adjustable height available
Min. Package Size:	4"W x 2"H compressible 6"W x 2"H non-compressible
Weight:	550 lbs.
Options:	Adjustable castors adding 3" to starting height

LEGEND	
	STOCK
	NON STOCK
	NOT AVAILABLE

GP-44											
		WIDTH									
		23	31	39	47	63	70	78	86	94	102
HEIGHT	19										
	23										
	31										
	39										
	47										
	55										
	63										

Automatic Strapping Machine

GP-44SP



Small Package

Features

- Capable of up to 30 straps/minute
- Programmable controlled with limited diagnostics
- Outside reel with automatic, waist-high straploading
- Electric, no-adjust reel brake
- Movable, magnetic control box to facilitate any operation position
- Safety switches on table tops and front door
- Loop ejector to eject accidentally actuated straps
- Long life heater blade with smoke exhaust system
- Power savings system. Motors run only during strap cycle
- Outside tension adjust knob
- Portable on casters
- Choice of 1/4", 3/8" or 1/2" strap. Available with 8"x8" or 9"x8" core
- Seven digit, non-reset maintenance counter
- Stainless steel table top
- Automatic re-feed mechanism

Specifications

Strapping Speed: Up to 30 straps/minute
Power: 110 volt single phase, others available
Tension: External, fully adjustable range
Strap Sizes: 1/4", 3/8", 1/2", polypropylene
Metric: 5, 6, 7, 9, 12mm polypropylene
Core Sizes: 8"x8" or 9"x8"
Machine Weight: 462 lbs.
Table Top Height: 31", adjustable height available
Min. Package Size: 3" wide x 3" high compressible
Options: Adjustable Casters Adding 3" to starting height

GP44 SIDE SEAL		
	WIDTH	
HEIGHT		23
	16	

LEGEND	
	STOCK

STRAPPING EQUIPMENT

Automatic Zinc Dichromate Arch Machine

GP-44ZN



Features

Designed and developed for food packaging industry strapping applications. The entire machine frame and covers have been dipped in zinc dichromate for corrosion resistance. In addition, critical components such as the feed/retract wheel, high tension arms and accumulator within the seal engine are constructed with stainless steel or zinc dichromate coated steel to prolong the serviceable life of the machine. The bottom of the machine has been enclosed to provide splash protection from room wash down requirements.

Specifications

Same basic specifications as our GP44

Strapping Speed: Up to 44 straps/minute
Tension: External, fully adjustable range
Power: 110 volt single phase, others available
Strap Sizes: 1/4", 3/8", 1/2", polypropylene
 Metric: 5, 6, 7, 9, 12mm polypropylene
Core Sizes: 8"x8" or 9"x8"
Table Top Height: 31", adjustable height available
Min. Package Size: 4"W x 2"H compressible
 6"W x 2"H non-compressible
Weight: 550 lbs.
Options: Adjustable castors adding 3" to starting height

Stock Arch Size: 31"W x 23"H

Designed for the Food Package Industry

Automatic Strapping Machine

PC-600AL



Features

- Lubrication free sealing mechanism
- Cycle start standard options –foot switch, push button or table top ball switch
- Capable of up to 25 straps/minute
- Simple, centralized controls
- Portable on casters
- Available in 3/8" (9mm) & 1/2" (12mm) strap on 8"x8" or 9"x8" core size
- Table Height = 31-1/2"
- Hinged, easily removable stainless steel table top with rollers, standard
- Automatic re-feed mechanism
- Weld-Cool switch for highly compressible packages or very rigid packages that need high tension
- Automatic strap loading
- Loop ejector to eject accidentally actuated straps

Specifications

Min. Package Size: 6" wide, 2" high
Max. Package Size: within arch size
Max. Tension: 180 lbs.
Speed: 2.5 seconds/cycle
Strap Sizes: 3/8", 1/2" polypropylene
 Metric: 9, 12mm polypropylene
Core Sizes: 8"x8" or 9"x8"
Electrical Supply: 110 VAC – standard
 440 VAC – 3 PH – optional
 220 VAC – 3 PH – optional

An Economical Choice With Automatic Loading!

LEGEND	
	STOCK
	NOT AVAILABLE

PC600AL		WIDTH				
		23	31	39	47	55
HEIGHT	16					
	23					
	31					
	39					
	47					
55						

STRAPPING EQUIPMENT

Automatic Strapping Machine

EC-2500



Features

- Clean design
- Up to 25 straps/minute
- Easy loading
- Few parts
- Loop ejector
- Moveable pendant
- Enclosed frame system
- Motor only runs during cycle
- Electronic step through cycle
- Electronic heater/cooling control
- Electronic tension control
- Foot pedal

Specifications

Min. Package Size:	6" x 6"
Max. Package Size:	Within arch size
Tension:	165 lbs.
Table Top Height:	32"
Electrical Supply :	110 VAC, 60 Hz, single phase
Weight:	385 lbs.
Core Sizes:	8"x8" or 9"x8"
Strap Sizes:	3/8", 1/2" polypropylene Metric: 9, 12mm polypropylene
Stock Arch Size:	33" wide x 23" high