

YOUR PROTECTION BY EXCELLENCE

RIPACK 2500 THE LIGHEST IN ITS CATEGORY





For regular shrink wrapping needs, the Ripack 2500 is the ideal tool for protecting your pallets. With adjustable power, it will adapt to the thickness of your films.

Compact and light, the Ripack 2500 is equipped with «cold nozzle» technology for unparalleled safety.

With its innovative quick and tool-free igniter change system, benefit from a reliable and robust shrink gun.

These heat tools are used in many sectors such as industry, construction, food, transport / logistics ...









TECHNICAL SPECIFICATIONS

| Power | 34 to 60 kW |
|--------------------|----------------------------|
| Pressure | 1,5 to 3,5 bars |
| Gas consumption | from 2,2 to 4 kg/h |
| Length/Height | 360/262 mm |
| Package dimensions | 460x330x140 mm |
| Weight | 940 g |
| Package weight | 4880 g |
| Noise level | < 85 dbA |
| Energy source | Propane gas or natural gas |
| | upon request |

Each gun is delivered in a carrying case with: 1 SECURIPACK 1.5-3.5 bar gas regulator, 1 8-meter hose with crimped connection, 1 key for tightening/ untightening the connections, 1 user manual with CE certificate.

EQUIPMENT SOLD SEPARATELY AND IN KIT



936 GAS BOTTLE TROLLEY



GAS HOSE REEL



MULTICOVER 950

All information and photos in this brochure refer to product specifications updated at the time of publication according to the date mentioned on this page. RIPACK® reserves the right to change the colors, materials, features and specifications of its products at any time. Some products may be shown with accessories and/or features not available in some countries. All rights reserved. Reproduction in any form and by any means is prohibited without previous authorization from RIPACK®. * guarantee for labor and parts; www.ripack.com



