X1S1664



16GA Wide Crown Stapler

Applications

Lathing

Specifications

Fastener Crown	1"
Fastener Length	1"- 2-1/2"
Magazine Capacity	150
Actuation Mode	Selective Actuation
Dimensions	14" x 3-1/2" x 9-3/4"
Weight	5.2 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.056 SCF
Noise Power Emissions per EN12549 Lw/	A,1s 106.5 dBA
Noise Pressure Emissions per EN12549 L	. pA,1s 105.0 dBA
Vibration Emissions per ISO-8662-11	3.39 m/s ²
Vibration Value Uncertainty per ISO-8662	-11 1.50 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Quick Clear Nose, Top Load Aluminum Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

Accessories

Air Filter (P-97454), Full Sequential Actuation Trigger (AS-21037), Lathing Safety Adaptor (AS-53085), Walking Stick Attachment (AS-99105)



For Best Results, Use Spotnails® Collated Fasteners

16GA 1" Wide Crown Staples (Similar to Bostitch® 16S2)

Sтоск No .	Length
Galvanized	
1608PG-10M	1"
1610PG-10M	1-1/4"
1612PG-10M	1-1/2"
1614PG-10M	1-3/4'
1616PG-10M	2"
1620PG-5M	2-1/2"



Division of Peace Industries, LTD.

P: 800-873-2239 / 847-259-1620 | F: 888-369-2588 | customerservice@spotnails.com SPOTNAILS.BIZ | SPOTNAILS.COM | RELIABILITYPROVIN.COM