X1S3640

SPOTNAILS®

16GA Wide Crown Stapler

Applications

Crate Assembly, Fastening Corrugated Packaging, Insulation Installation, Lathing, Packaging, Pallet Assembly, Roofing, Shingle Installation, Wall Panel Construction

Specifications

Fastener Crown	1"
Fastener Length	1/2"- 1-1/2"
Magazine Capacity	150
Actuation Mode	Selective Actuation
Dimensions	14" x 3-1/2" x 9-3/4"
Weight	5.1 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.042 SCF
Noise Power Emissions per EN12549 LwA,1s	106.5 dBA
Noise Pressure Emissions per EN12549 LpA,1s	105.0 dBA
Vibration Emissions per ISO-8662-11	3.39 m/s^2
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s^2

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Quick Clear Nose, Top Load Aluminum Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil, Wear Plate Filler Kit

Accessories

Air Filter (P-97454), Full Sequential Actuation Trigger (AS-21037), Lathing Safety Adaptor (AS-53085), Long Magazine (X1S3640LM), Roofing Safety Adaptor (AS-53086), Shingle Guide Adaptor (AS-97296), Walking Stick Attachment (AS-99105)

For Best Results, Use Spotnails® Collated Fasteners

16GA 1" Wide Crown Staples

(Similar to Senco® P/Duo-Fast® 1700)

STOCK NO.	LENGTH
Galvanized	
3604PG-10M	1/2"
3605PG-10M	5/8"
3606PG-10M	3/4"
3607PG-10M	7/8"
3608PG-10M	1"
3610PG-10M	1-1/4"
3612PG-10M	1-1/2"
304 Stainless Steel	
3608PS-10M	1"

RELIABILITY Provin™