



TECHNICAL DATA SHEET

HM 130

PRODUCT NUMBER

LAST UPDATE: 12/02/10

HOT MELT PRODUCT

Low melt Case and carton sealing/tray forming

GENERAL INFORMATION

HM-130 is a fast setting hot melt for packaging operations. It exhibits excellent bonds on a wide variety of board and paper stocks. It has excellent heat stability and low viscosity for good machining on all standard hot melt application equipment. HM -130 has good freezer resistance and has shown to be as effective as a 350 F hot melt in high heat conditions. HM-130 exhibits aggressive tack, which is important where short compression sections are encountered.



PHYSICAL PROPERTIES

Application Temperature	250°F
Color	Opaque Yellow
Form:	Slats/Chicklet
Softening Point	169°F
Viscosity @ 250°F	900 cPs
Speed of set	Fast

25 lbs / case (net)
1750 lbs/ pallet (net)

HANDLING INSTRUCTIONS

To avoid accidental contamination, keep container covered as soon as sufficient hot melt has been removed for use. Do not store in high temperatures.

SAFETY INSTRUCTIONS

No health hazards are expected with HM-130 in its solid form. Once melted, it is like any hot liquid in that it can produce severe burns. Care should be taken to avoid getting the hot liquid adhesive on the skin. If this occurs, flush the affected area with large amounts of cold water. Do not try to remove the solidified hot melt. Seek medical attention immediately.

FDA STATUS

All ingredients in HM-130 are approved under the Federal regulation 21 CFR 175.105 which related to incidental contact of adhesive with food.

CONSULT MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION.
7860 Zeigler Blvd. P.O. Box 8737 (36689) Mobile, AL 36608
Phone: 251-633-5034 Fax: 251-633-4210